

# Prothese de main arduino

[Prothese main arduino 001](#)

[Capteur pour muscle Myoware](#)

[Electrodes pour muscle](#)

## Main Robotisée HackBerry



[Fabrication collaborative Main-robotisée site e-nable](#)

[Doc Main robotisée](#)

[Programme main robotisée HackBerry GitHub](#)

## Programme HackBerry.ino version V1.0 MK2

[HackberryMk2v1.0.ino](#)

```
/*
 *  Arduino micro code for HACKberry Mk2.
 *  Originally created by exiii Inc.
 *  edited by Kouki Shinjo on 2018/04/26
 */
#include <Servo.h>

//Settings
const boolean isRight = 0;//right:1, left:0
const int outThumbMax = 95;//right:open, left:close
const int outIndexMax = 100;//right:open, left:close
const int outOtherMax = 75;//right:open, left:close
const int outThumbMin = 10;//right:close, left:open
const int outIndexMin = 0;//right:close, left:open
```

```
const int outOtherMin = 20;//right:close, left:open
const int speedMax = 6;
const int speedMin = 0;
const int speedReverse = -3;
const int thSpeedReverse = 15;//0-100
const int thSpeedZero = 30;//0-100
const boolean onSerial = 0; // 1 is not recommended

//Pin
int pinButtonCalib; //start calibration
int pinButtonTBD; // No function implemented yet.
int pinButtonThumb; // open/close thumb
int pinButtonOther; //lock/unlock other three fingers
int pinServoIndex;
int pinServoOther;
int pinServoThumb;
int pinSensor; //sensor input

//Hardware
Servo servoIndex; //index finger
Servo servoOther; //other three fingers
Servo servoThumb; //thumb

//Software
boolean isThumbOpen = 1;
boolean isOtherLock = 0;
int swCount0,swCount1,swCount2,swCount3 = 0;
int sensorValue = 0; // value read from the sensor
int sensorMax = 700;
int sensorMin = 0;
int speed = 0;
int position = 0;
const int positionMax = 100;
const int positionMin = 0;
int prePosition = 0;
int outThumb,outIndex,outOther = 90;
int
outThumbOpen,outThumbClose,outIndexOpen,outIndexClose,outOtherOpen,outOtherClose;

void setup() {
    if (onSerial) Serial.begin(9600);

    // Pin Configuration
    pinButtonCalib = A6;// A4 sur Arduino Uno pour test Calibration
    pinButtonTBD = A7;// A5 sur Arduino Uno pour test
    pinButtonThumb = A0;// Verrouillage pouce
    pinButtonOther = 10;// Verrouillage 3 doigts
    pinServoIndex = 5;// Servo pour l'index
    pinServoOther = 6;// Servo pour 3 doigts
    pinServoThumb = 9;// Servo pour le pouce
```

```
pinSensor      = A1; // Capteur de pression

if(isRight){
    outThumbOpen=outThumbMax; outThumbClose=outThumbMin;
    outIndexOpen=outIndexMax; outIndexClose=outIndexMin;
    outOtherOpen=outOtherMax; outOtherClose=outOtherMin;
} else {
    outThumbOpen=outThumbMin; outThumbClose=outThumbMax;
    outIndexOpen=outIndexMin; outIndexClose=outIndexMax;
    outOtherOpen=outOtherMin; outOtherClose=outOtherMax;
}
servoIndex.attach(pinServoIndex); //index
servoOther.attach(pinServoOther); //other
servoThumb.attach(pinServoThumb); //thumb

pinMode(pinButtonCalib, INPUT_PULLUP);
pinMode(pinButtonTBD, INPUT_PULLUP);
pinMode(pinButtonThumb, INPUT_PULLUP);
pinMode(pinButtonOther, INPUT_PULLUP);
}

void loop() {
    //==waiting for calibration==
    if(onSerial) Serial.println("=====Waiting for Calibration=====");
    while (1) {
        servoIndex.write(outIndexOpen);
        servoOther.write(outOtherOpen);
        servoThumb.write(outThumbOpen);
        if(onSerial) serialMonitor();
        delay(10);
        if (readButton(pinButtonCalib) == LOW) {
            calibration();
            break;
        }
    }
    //==control==
    position = positionMin;
    prePosition = positionMin;
    while (1) {
        if (readButton(pinButtonCalib) == LOW) swCount0 += 1;
        else swCount0 = 0;
        if (swCount0 == 10) {
            swCount0 = 0;
            calibration();
        }
        if (readButton(pinButtonTBD) == LOW) swCount1 += 1;
        else swCount1 = 0;
        if (swCount1 == 10) {
            swCount1 = 0;
            // Do something here
            while (readButton(pinButtonTBD) == LOW) delay(1);
        }
    }
}
```

```
        }
        if (readButton(pinButtonThumb) == LOW) swCount2 += 1;
        else swCount2 = 0;
        if (swCount2 == 10) {
            swCount2 = 0;
            isThumbOpen = !isThumbOpen;
            while (readButton(pinButtonThumb) == LOW) delay(1);
        }
        if (readButton(pinButtonOther) == LOW) swCount3 += 1;//A3
        else swCount3 = 0;
        if (swCount3 == 10) {
            swCount3 = 0;
            isOtherLock = !isOtherLock;
            while (readButton(pinButtonOther) == LOW) delay(1);
        }

        sensorValue = readSensor();
        delay(25);
        if(sensorValue<sensorMin) sensorValue=sensorMin;
        else if(sensorValue>sensorMax) sensorValue=sensorMax;
        sensorToPosition();

        outIndex = map(position, positionMin, positionMax,
outIndexOpen, outIndexClose);
        servoIndex.write(outIndex);
        if (!isOtherLock){
            outOther = map(position, positionMin, positionMax,
outOtherOpen, outOtherClose);
            servoOther.write(outOther);
        }
        if(isThumbOpen) servoThumb.write(outThumbOpen);
        else servoThumb.write(outThumbClose);
        if(onSerial) serialMonitor();
    }
}

/*
* functions
*/
boolean isDigitalPin(const int pin) {
    return (pin >= 0) && (pin <= 19) ? true : false;
}

boolean readButton(const int pin) {
    if ( isDigitalPin(pin) ) {
        return digitalRead(pin);
    } else {
        if (analogRead(pin) > 512) return HIGH;
        else return LOW;
    }
}
```

```
int readSensor() {
    int i, sval;
    for (i = 0; i < 10; i++) {
        sval += analogRead(pinSensor);
    }
    sval = sval/10;
    return sval;
}

void sensorToPosition(){
    int tmpVal = map(sensorValue, sensorMin, sensorMax, 100, 0);
    if(tmpVal<thSpeedReverse) speed=speedReverse;
    else if(tmpVal<thSpeedZero) speed=speedMin;
    else speed=map(tmpVal,40,100,speedMin,speedMax);
    position = prePosition + speed;
    if (position < positionMin) position = positionMin;
    if (position > positionMax) position = positionMax;
    prePosition = position;
}

void calibration() {
    outIndex=outIndexOpen;
    servoIndex.write(outIndexOpen);
    servoOther.write(outOtherClose);
    servoThumb.write(outThumbOpen);
    position=positionMin;
    prePosition=positionMin;

    delay(200);
    if(onSerial) Serial.println("=====calibration start=====");

    sensorMax = readSensor();
    sensorMin = sensorMax - 50;
    unsigned long time = millis();
    while ( millis() < time + 4000 ) {
        sensorValue = readSensor();
        delay(25);
        if ( sensorValue < sensorMin ) sensorMin = sensorValue;
        else if ( sensorValue > sensorMax )sensorMax = sensorValue;

        sensorToPosition();
        outIndex = map(position, positionMin, positionMax,
outIndexOpen, outIndexClose);
        servoIndex.write(outIndex);

        if(onSerial) serialMonitor();
    }
    if(onSerial) Serial.println("=====calibration finish=====");
    return;
}
```

```
void serialMonitor(){
    Serial.print("Min="); Serial.print(sensorMin);
    Serial.print(",Max="); Serial.print(sensorMax);
    Serial.print(",sensor="); Serial.print(sensorValue);
    Serial.print(",speed="); Serial.print(speed);
    Serial.print(",position="); Serial.print(position);
    Serial.print(",outIndex="); Serial.print(outIndex);
    Serial.print(",isThumbOpen="); Serial.print(isThumbOpen);
    Serial.print(",isOtherLock="); Serial.println(isOtherLock);
}
```

## Programme HackBerry.ino version V3.1 MK2

[Hackberryv31MK2\\_V31.ino](#)

```
/*
 * Arduino micro code for HACKberry.
 * Originally created by exiii Inc.
 * edited by Genta Kondo on 2017/6/11
 */
#include <Servo.h>

//Settings
const boolean isRight = 1;//right:1, left:0

//For right hand, find optimal values of ThumbMin, IndexMax and
//OtherMax first.
//For left hand, find optimal values of ThumbMax, IndexMin and OtherMin
//first.
//Then, calculate the remaining values by following rules.
//Difference of ThumbMin and ThumbMax is 86
//Difference of IndexMin and IndexMax is 117
//Difference of OtherMin and OtherMax is 55

const int outThumbMax = 170;//right:open, left:close
const int outIndexMax = 142;//right:open, left:close
const int outOtherMax = 96;//right:open, left:close

const int outThumbMin = 170-86;//right:close, left:open
const int outIndexMin = 140-117; //right:close, left:open
const int outOtherMin = 95-55;//right:close, left:open

const int speedMax = 6;
const int speedMin = 0;
const int speedReverse = -3;
const int thSpeedReverse = 15;//0-100
const int thSpeedZero = 30;//0-100
```

```
const boolean onSerial = 0; //Mk2 doesn't use serial monitor

//Hardware
Servo servoIndex; //index finger
Servo servoOther; //other three fingers
Servo servoThumb; //thumb
int pinCalib; //start calibration
//int pinTBD;
int pinThumb; // open/close thumb
int pinOther; //lock/unlock other three fingers
int pinSensor = A1; //sensor input

//Software
boolean isThumbOpen = 1;
boolean isOtherLock = 0;
int swCount0,swCount1,swCount2,swCount3 = 0;
int sensorValue = 0; // value read from the sensor
int sensorMax = 700;
int sensorMin = 0;
int speed = 0;
int position = 0;
const int positionMax = 100;
const int positionMin = 0;
int prePosition = 0;
int outThumb,outIndex,outOther = 90;
int
outThumbOpen,outThumbClose,outIndexOpen,outIndexClose,outOtherOpen,outOtherClose;

void setup() {
  Serial.begin(9600);
  if(isRight){
    pinCalib = A6;
    //pinTBD = A7;
    pinThumb = A0;
    pinOther = 10;
    outThumbOpen=outThumbMax; outThumbClose=outThumbMin;
    outIndexOpen=outIndexMax; outIndexClose=outIndexMin;
    outOtherOpen=outOtherMax; outOtherClose=outOtherMin;
  }
  else{
    pinCalib = A6;
    //pinTBD = A7;
    pinThumb = A0;
    pinOther = 10;
    outThumbOpen=outThumbMin; outThumbClose=outThumbMax;
    outIndexOpen=outIndexMin; outIndexClose=outIndexMax;
    outOtherOpen=outOtherMin; outOtherClose=outOtherMax;
  }
  servoIndex.attach(5); //index
  servoOther.attach(6); //other
```

```
servoThumb.attach(9); //thumb
//pinMode(pinCalib, INPUT); //A6
//digitalWrite(pinCalib, HIGH);
//pinMode(pinTBD, INPUT); //A5
//digitalWrite(pinTBD, HIGH);
pinMode(pinThumb, INPUT); //A4
digitalWrite(pinThumb, HIGH);
pinMode(pinOther, INPUT); //A3
digitalWrite(pinOther, HIGH);
}

void loop() {
//==waiting for calibration==
if(onSerial) Serial.println("=====Waiting for Calibration=====");
while (1) {
    servoIndex.write(outIndexOpen);
    servoOther.write(outOtherOpen);
    servoThumb.write(outThumbOpen);
    if(onSerial) serialMonitor();
    delay(10);
    if (DigitalRead(pinCalib) == LOW) {
        calibration();
        break;
    }
}
//==control==
position = positionMin;
prePosition = positionMin;
while (1) {
    if (DigitalRead(pinCalib) == LOW) swCount0 += 1;
    else swCount0 = 0;
    if (swCount0 == 10) {
        swCount0 = 0;
        calibration();
    }
    if (digitalRead(pinThumb) == LOW) swCount2 += 1;
    else swCount2 = 0;
    if (swCount2 == 10) {
        swCount2 = 0;
        isThumbOpen = !isThumbOpen;
        while (digitalRead(pinThumb) == LOW) delay(1);
    }
    if (digitalRead(pinOther) == LOW) swCount3 += 1; //A3
    else swCount3 = 0;
    if (swCount3 == 10) {
        swCount3 = 0;
        isOtherLock = !isOtherLock;
        while (digitalRead(pinOther) == LOW) delay(1);
    }
}

sensorValue = readSensor();
```

```
    delay(25);
    if(sensorValue<sensorMin) sensorValue=sensorMin;
    else if(sensorValue>sensorMax) sensorValue=sensorMax;
    sensorToPosition();

    outIndex = map(position, positionMin, positionMax, outIndexOpen,
outIndexClose);
    servoIndex.write(outIndex);
    if (!isOtherLock){
        outOther = map(position, positionMin, positionMax, outOtherOpen,
outOtherClose);
        servoOther.write(outOther);
    }
    if(isThumb0open) servoThumb.write(outThumbOpen);
    else servoThumb.write(outThumbClose);
    if(onSerial) serialMonitor();
}

/*
 * functions
 */
int readSensor() {
    int i, sval;
    for (i = 0; i < 10; i++) {
        sval += analogRead(pinSensor);
    }
    sval = sval/10;
    return sval;
}

void sensorToPosition(){
    int tmpVal = map(sensorValue, sensorMin, sensorMax, 100, 0);
    if(tmpVal<thSpeedReverse) speed=speedReverse;
    else if(tmpVal<thSpeedZero) speed=speedMin;
    else speed=map(tmpVal,40,100,speedMin,speedMax);
    position = prePosition + speed;
    if (position < positionMin) position = positionMin;
    if (position > positionMax) position = positionMax;
    prePosition = position;
}


void calibration() {
    outIndex=outIndexOpen;
    servoIndex.write(outIndexOpen);
    servoOther.write(outOtherClose);
    servoThumb.write(outThumbOpen);
    position=positionMin;
    prePosition=positionMin;

    delay(200);
```


```
if(onSerial) Serial.println("=====calibration start=====");  
  
sensorMax = readSensor();  
sensorMin = sensorMax - 50;  
unsigned long time = millis();  
while ( millis() < time + 4000 ) {  
    sensorValue = readSensor();  
    delay(25);  
    if ( sensorValue < sensorMin ) sensorMin = sensorValue;  
    else if ( sensorValue > sensorMax ) sensorMax = sensorValue;  
  
    sensorToPosition();  
    outIndex = map(position, positionMin, positionMax, outIndexOpen,  
outIndexClose);  
    servoIndex.write(outIndex);  
  
    if(onSerial) serialMonitor();  
}  
if(onSerial) Serial.println("=====calibration finish=====");  
}  
  
void serialMonitor(){  
    Serial.print("Min="); Serial.print(sensorMin);  
    Serial.print(",Max="); Serial.print(sensorMax);  
    Serial.print(",sensor="); Serial.print(sensorValue);  
    Serial.print(",speed="); Serial.print(speed);  
    Serial.print(",position="); Serial.print(position);  
    Serial.print(",outIndex="); Serial.print(outIndex);  
    Serial.print(",isThumbOpen="); Serial.print(isThumbOpen);  
    Serial.print(",isOtherLock="); Serial.println(isOtherLock);  
}  
  
boolean DigitalRead(const int pin) {  
    if (analogRead(pin) > 512) return 1;  
    else return 0;  
}
```

## Simulation main sur Tinkercad

### Cablage Arduino Uno et servoMoteurs



## Schema



## Programme HackBerry\_Test\_tinkercad.ino version V1.0

[Main\\_robot\\_0011.ino](#)

```
#include <Servo.h>

//Pin
int pinButtonCalib; //start calibration
int pinButtonTBD; // No function implemented yet.
int pinButtonThumb; // open/close thumb
int pinButtonOther; //lock/unlock other three fingers
int pinServoIndex;
int pinServoOther;
int pinServoThumb;
int pinSensor; //sensor input

//Software
int sensorValue = 0;
int memPouce = 0;
int memIndex = 0;
int mem3Dgts = 0;

//Hardware
Servo servoIndex; //index
Servo servoOther; //3doigts
Servo servoThumb; //pouce

//Valeurs mini/max servos
const int outThumbMax = 170;//valeur max servo pouce
const int outIndexMax = 142;//valeur max servo index
const int outOtherMax = 96;//valeur max servo 3doigts

const int outThumbMin = 170-86;//valeur min servo pouce 170-86=84
const int outIndexMin = 140-117; //valeur min servo index 140-117= 23
const int outOtherMin = 95-55;//valeur min servo 3doigts 95-55 = 40

void setup() {
    Serial.begin(9600);

    // Pin Configuration
    pinButtonCalib = A4;// A6 sur Hackberry pour test Calibration --
validation index
    pinButtonTBD = A5;// A7 sur Hackberry pour test
    pinButtonThumb = A0;// Verrouillage pouce -- validation pouce
    pinButtonOther = 10;// Verouillage 3 doigts -- validation 3doigts
    pinServoIndex = 5;// Servo pour l'index
    pinServoOther = 6;// Servo pour 3 doigts
    pinServoThumb = 9;// Servo pour le pouce
    pinSensor = A1; // Capteur de pression

    servoIndex.attach(pinServoIndex);//index
    servoOther.attach(pinServoOther);// 3 doigts
    servoThumb.attach(pinServoThumb);//Pouce
```

```
pinMode(pinButtonCalib, INPUT_PULLUP);
pinMode(pinButtonTBD, INPUT_PULLUP);
pinMode(pinButtonThumb, INPUT_PULLUP);
pinMode(pinButtonOther, INPUT_PULLUP);
}

void loop() {
    sensorValue = 0;

    if ( digitalRead(pinButtonThumb) == HIGH ){
        memPouce = 1;
        memIndex = 0;
        mem3Dgts = 0;
    }
    if ( digitalRead(pinButtonCalib) == HIGH ){
        memPouce = 0;
        mem3Dgts = 0;
        memIndex = 1;
    }
    if ( digitalRead(pinButtonOther) == HIGH ){
        memPouce = 0;
        mem3Dgts = 1;
        memIndex = 0;
    }

    if (memPouce == 1){
        sensorValue = analogRead(pinSensor);
        delay(25);
        sensorValue = map(sensorValue, 0, 1023, outThumbMin, outThumbMax);
        Serial.print("sensor pouce= "); Serial.println(sensorValue);
        servoThumb.write(sensorValue);
        delay(15);
    }
    if (memIndex == 1){
        sensorValue = analogRead(pinSensor);
        delay(25);
        sensorValue = map(sensorValue, 0, 1023,outIndexMin, outIndexMax);
        Serial.print("sensor index= "); Serial.println(sensorValue);
        servoIndex.write(sensorValue);
        delay(15);
    }
    if (mem3Dgts == 1){
        sensorValue = analogRead(pinSensor);
        delay(25);
        sensorValue = map(sensorValue, 0, 1023,outOtherMin, outOtherMax);
        Serial.print("sensor doigts= "); Serial.println(sensorValue);
        servoOther.write(sensorValue);
        delay(15);
    }
}
```

}

From:

<http://chanterie37.fr/fablab37110/> - Castel'Lab le Fablab MJC de Château-Renault



Permanent link:

<http://chanterie37.fr/fablab37110/doku.php?id=start:arduino:mains&rev=1667209925>

Last update: **2023/01/27 16:08**